



Southern Pipe, Inc.

P. O. Box 606, 135 Random Drive, New London, NC 28127
 Phone: 704-463-5202 Fax: 704-463-5203 www.southern-pipe.com

**TYPE EB – 20 (ENCASED BURIAL) TC-6
 RIGID PVC NONMETALLIC CONDUIT
 FOR CONCRETE ENCASEMENT UNDERGROUND**

Southern Pipe Type EB-20 (Encased Burial Utility Duct) rigid PVC conduit is manufactured for use in outside concrete encasement applications. Type EB-20 is manufactured in accordance with the following industry standards:

Underwriters Laboratory, Inc.® (UL)	651-A
National Electrical Manufacturers Association (NEMA)	TC-6
American Society for Testing and Materials (ASTM)	F-512

SIZE	PART NUMBER	DESCRIPTION	MIN WALL	O.D.	WEIGHT PER 100 FEET	PALLET QTY
2"	62820	20 FT/B.E.	.060	2.375	36.4	2800
3"	62630	20 FT/B.E.	.061	3.500	61	1760
3 1/2"	62635	20 FT/B.E.	.072	4.000	83	1260
4"	62640	20 FT/B.E.	.082	4.500	99	1140
5"	62650	20 FT/B.E.	.103	5.563	142	760
6"	62660	20 FT/B.E.	.125	6.625	199	520

Rated for 90° C



RUS listed
 Sunlight Resistant

MANUFACTURER OF QUALITY PVC ELECTRICAL CONDUIT PRODUCTS



Southern Pipe, Inc.

P. O. Box 606, 135 Random Drive, New London, NC 28127
Phone: 704-463-5202 Fax: 704-463-5203 www.southern-pipe.com

**TYPE DB-60 (DIRECT BURIAL) TC-6
RIGID PVC NONMETALLIC CONDUIT
FOR DIRECT BURIAL UNDERGROUND**

Southern Pipe Type DB-60 (DIRECT BURIAL) rigid PVC conduit is manufactured for direct burial underground. Type DB-60 TC-6 is manufactured in accordance with the following industry standards.

National Electrical Manufacturers Association (NEMA)
American Society for Testing and Materials (ASTM)

TC-6
F-512

SIZE	PART NUMBER	DESCRIPTION	MIN WALL	O.D.	WEIGHT PER 100 FEET	PALLET QTY
2"	62820	20 FT/B.E.	.060	2.375	36.4	2800
3"	62830	20 FT/B.E.	.092	3.500	76	1760
3 1/2"	62835	20 FT/B.E.	.107	4.000	114	1260
4"	62840	20 FT/B.E.	.121	4.500	135	1140
5"	62850	20 FT/B.E.	.152	5.563	191	760
6"	62860	20 FT/B.E.	.182	6.625	260	520

RUS listed

MANUFACTURER OF QUALITY PVC ELECTRICAL CONDUIT PRODUCTS